



Kährs

Grande Collection



OAK CITADELLE

This single-strip oak floor from the Grande Collection features a delicate grey stain, which allows the softer sepia tones in the timber to come through. Each board is meticulously hand-scraped, which enhances the rustic appearance of the floor. Four-sided bevelling at the edges ensures a classic, full plank look and feel. This product must be oiled after installation and prior to use.

PRODUCT DETAILS

| | |
|-------------------------------------|--|
| Product type / Construction | Wood Floors / 3-layer parquet |
| Article Number / EAN Code | 201XACEKFMKE280 / 7393969033534 |
| Design / Wood Species | Plank / Oak |
| Surface treatment / Natural/Stained | Oil / Stained |
| Design features | Handscraped, Bevelled 4-sided |
| Width x Length x Thickness | 260 x 2800 x 20 mm |
| Weight per package / per m2 | 38 kg / 13.1 kg |
| Area per package / per pallet | 2.91 m ² / 81.48 m ² |
| Grading | Variation |
| Joint | Tongue & Groove |
| Installation method | Glue-down |
| Floor heating | No |
| Wear leayer material / thickness | Hardwood / 5 mm |
| Resandable | 2-4 times |
| Backside material | Veneer |
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |

PRODUCT DETAILS

| | | |
|-------------------------------------|------------------------|------------|
| Warranty | 30 years | |
| TECHNICAL PROPERTIES | | |
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density | >500 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,125 W/mK |
| Thermal Resistance R-Value | .16 (m2K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers. Grande products may continue to develop their rustic nature after the floor has been installed; splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2026-04-10

1 (2)

