



CITADELLE OAK

This single-strip oak floor from the Grande Collection features a delicate grey stain, which allows the softer sepia tones in the timber to come through. Each board is meticulously hand-scraped, which enhances the rustic appearance of the floor. Four-sided bevelling at the edges ensures a classic, full plank look and feel. This product must be oiled after installation and prior to use.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PRO | TECHNICAL PROPERTIES | | |
|--|---|----------------------|-------------------|---|---------------------------------------|-------------|--|
| Article Number | 201XACEKFMKE280 | Wood Species | Oak | Moisture | EN13183 | 7%±2% | |
| EAN Code | 7393969033534 | Design | 1-strip | content | | | |
| Surface Treatment | Oil This floor should be oiled immediately after installation. | Grading | Variation | Minimun Mean | Minimun Mean Density kg/m³ >500 kg/m³ | | |
| | | Range | Kährs Supreme | Reaction To Fire | EN13501-1 | Dfl-s1 | |
| | | Collection | Grande Collection | Formaldehyde | EN717-1 | E1 | |
| Refining Treatment | Handscraped, Bevelled 4- sided | Natural/Stained | Stained | Emission | | | |
| | | Brinell Value | 3,7 | Content PCP | CEN/TR14823 | ≤ 5 x 10-6n | |
| Dimensions | 260 x 2800 mm | Joint | Tongue & Groove | Breaking | EN1533 | NPD | |
| Weight per Package | 38 kg | Floor heating | No | Strength N/mm² | | | |
| Area per Package | 2.9 m ² | Wear-layer material | Hardwood | Thermal | EN12664 | 0,125 W/mK | |
| Package info | Packages may contain start and stop boards. | Wear Layer Thickness | 5 mm | Conductivity | | | |
| | | Backside material | Veneer | Thermal Resista | Thermal Resistance R-Value | | |
| DETAIL DESCRIPTION | | | 20 mm | Biological Durability | EN350-2 | Class 1 | |
| Naturally occuring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers. Grande products may continue to | | Installation method | Glue-down | CARB2 | | Compliant | |
| | | | | Slipperiness | CEN/TS15676 | NPD | |

COLOUR CHANGE

Stained product - noticable color change over time.

develop their rustic nature after the floor has been installed, splits and cracks that occur after installation are normal and should be considered

part of the timbers natural character.





Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.