



OAK VAPOR

The semi-transparent white stain on this brushed, 2-strip oak floor from the Lumen Collection balances light and dark contrasts in the wood, allowing the subtle warm oak tones to softly filter through. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

| PRODUCT DETAILS | |
|-----------------------------|---|
| Product type / Construction | Wood Floors / 3-layer parquet |
| Article Number / EAN Code | 152N7BEKB4KW240 / 7393969044790 |
| Design / Wood Species | 2-strip / Oak |
| Surface treatment / | Ultra matt lacquer / Stained |
| Natural/Stained | |
| Design features | Brushed |
| Width x Length x Thickness | 200 x 2423 x 15 mm |
| Weight per package / per | 23 kg / 7.9 kg |
| m2 | |
| Area per package / per | 2.91 m ² / 130.95 m ² |
| pallet | |
| Grading | Lively |
| Joint | Woodloc® 5S |
| Installation method | Floating, Glue-down |
| Floor heating | Yes |
| Wear leayer material / | Hardwood / 3.5 mm |
| thickness | |
| Resandable | 2-3 times |
| Core material | Pine/Spruce/Alder |
| Backside material | Spruce |

| | F | PRC | D | UC | ΓD | ΕT | All | LS |
|--|---|-----|---|----|----|----|-----|----|
|--|---|-----|---|----|----|----|-----|----|

| Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 | |
|----------------------------|-----------------|-------|
| range | | |
| LRV / LRV Std1 | 45 / 5.1 | |
| Warranty | 30 years | |
| - TECHNICAL PROPERTIES | | |
| - Moisture content | EN13183 | 7%±2% |

| TECHNICAL PROPERTIES | 5 | |
|-------------------------|-------------|------------|
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >500 kg/m³ |
| kg/m³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,11W/mK |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |



Slip resistance







CEN/TS15676





NPD







DETAILED DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes medium sound and black knots. Knots may vary in size and numbers.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticeable color change over time

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

Other products in this collection



OAK GLOW



OAK VAPOR



OAK DIM



OAK RIME



OAK MIST



OAK TWILIGHT



OAK ECLIPSE



OAK DAWN



OAK DUSK