OAK LIMESTONE

PRODUCT DETAILS

Construction	3-layer engineered
Article Number / EAN Code	153N0BEK0WKW240 / 7393969032629
Design / Wood Species	3-strip / White Oak
Surface Treatment / Natural/Stained	Matte finish / Stained
Refining Treatment	Brushed
Width x Length x Thickness	7 7/8 x 95 3/8 x 5/8"
Weight per package / per m2	50.7 lbs / 17.5 lbs
Area per package / per pallet	31.2 sqft / 1400.4 sqft
Grading	Lively
Joint	Woodloc® 5S
Installation method	Floating, Glue-Down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 1/8"
Resandable	2 times
Core material	Pine/Spruce lamella
Brinell value / range	3,7 / 2.2 - 5.9

PRODUCT DETAILS

LRV / LRV Std1	51.8 / 6.1
Warranty	25 years

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m³		>500 kg/m³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

TSCA TITLE VI & CARB P2 Compliant

DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown. Will include sapwood.
The product includes medium sound and black knots. Knots may vary in size and numbers.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection


Alloy


Oak Pale


Oak Creme


Oak Granite


Oak Limestone


Oak Lava