



OAK SORRENTO

The natural variations in the timber used in this 3-strip oak floor from the Sand Collection are enhanced by a soft white finish, resulting in an elegant and light expression. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

PRODUCT DETAILS

Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	153N38EK0VKW240 / 7393969027229
Design / Wood Species	3-strip / Oak
Surface treatment / Natural/Stained	Matt lacquer / Stained
Width x Length x Thickness	200 x 2423 x 15 mm
Weight per package / per m2	23 kg / 7.93 kg
Area per package / per pallet	2.91 m² / 130.1 m²
Grading	Variation
Joint	Woodloc® 5S
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 3.5 mm
Resandable	2-3 times
Core material	Pine/Spruce lamella
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9
LRV / LRV Std1	37 / 3.2

PRODUCT DETAILS

Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density	>500 kg/m³	
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

Even colour with minor variations.
Small sized knots in limited numbers allowed.
Colour change: Stained product - noticable color change over time.
Packages may contain start and stop boards.

Other products in this collection



OAK AMALFI



OAK RÜGEN



OAK ESTORIL



OAK SORRENTO



OAK PORTOFINO



OAK BRIGHTON



ASH SKAGEN



ASH SANDVIG



ASH FALSTERBO