



OAK SORRENTO

Oak Sorrento, a classic oak floor from Kahrs, available with white-pigmented matt lacquer which brings out the wood's natural variations and gives the surface elegance and lightness.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	153N38EK0VKW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969027229	Design	3-strip	Minimum Mean Density kg/m³ >500 kg/m³		
Surface Treatment	Matt lacquer	Grading	Variation	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	200 x 2423 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	23 kg	Collection	Sand Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.9 m²	Natural/Stained	Stained	Breaking Strength N/mm²	EN1533	NPD
Area per pallet	130.1 m²	Brinell Value	3,7	Thermal Conductivity	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Joint	Woodloc® 5S	Thermal Resistance R-Value		.11 (m2K/W)
DETAIL DESCRIPTION		Floor heating	Yes	Biological Durability	EN350-2	Class 1
			25 years	CARB2		Compliant
		Wear-layer material	Hardwood	Slipperiness	CEN/TS15676	NPD
COLOUR CHANGE		Wear Layer Thickness	3.5 mm			
		Core material	Pine/Spruce lamella			
			15 mm			
		Installation method	Floating, Glue-down			
		Surface Colour	White			

Other products in this collection



Oak Estoril



Oak Sorrento



Oak Portofino



Oak Brighton



Ash Skagen



Ash Falsterbo

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.