

OAK STRAW

The naturally oiled finish on this rustic, single-strip oak floor from the Artisan Collection brings out the colour variations in the timber, which range from toasted cinnamon to burnt toffee hues. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

	TECHNICAL PROPERTIES	5	
Wood Floors / 3-layer parquet	Moisture content	EN13183	7%±2%
151XCDEKFZKW195 / 7393969045292	Minimun Mean Density		>500 kg/m³
Plank / Oak	kg/m ³		
Oil / Natural	Reaction To Fire	EN13501-1	Dfl-s1
	Formaldehyde Emission	EN717-1	E1
Bevelled 4-sided, Brushed, Handscraped	Content PCP	CEN/TR14823	≤ 5 ppm
190 x 1900 x 15 mm	Breaking Strength N/mm ²	EN1533	NPD
17 kg / 7.73 kg	Thermal Conductivity	EN12664	0,11W/mK
	Biological Durability	EN350-2	Class 1
2.17 m ² / 75.95 m ²	CARB2		Compliant
	Slip resistance	CEN/TS15676	NPD
Dynamic			
Woodloc® 5G	TITLE VI		
Glue-down, Floating	CARB P2 Compliant BASTA		
Yes			
Hardwood / 3.5 mm			
2-3 times			
Pine/Spruce			
30 years			
	151XCDEKFZKW195 / 7393969045292Plank / OakOil / NaturalBevelled 4-sided, Brushed, Handscraped190 x 1900 x 15 mm17 kg / 7.73 kg2.17 m² / 75.95 m²DynamicWoodloc® 5GGlue-down, FloatingYesHardwood / 3.5 mm2.3 timesPine/Spruce	Wood Floors / 3-layer parquetMoisture content151XCDEKFZKW195 / 7393969045292Minimun Mean DensityPlank / Oakkg/m³Oil / NaturalReaction To FireFormaldehyde EmissionFormaldehyde EmissionBevelled 4-sided, Brushed, HandscrapedContent PCP190 x 1900 x 15 mmBreaking Strength N/mm²17 kg / 7.73 kgThermal ConductivityBiological DurabilityBiological Durability2.17 m² / 75.95 m²CARB2DynamicSlip resistanceVoodloc® 5GThermalGlue-down, FloatingYesHardwood / 3.5 mmEASTA2-3 timesPine/Spruce	Wood Floors / 3-layer parquetMoisture contentEN13183151XCDEKFZkW195 / 7393969045292Minimun Mean DensityPlank / Oakkg/m³Oil / NaturalReaction To FireEN13501-1Formaldehyde EmissionEN1717-1Bevelled 4-sided, Brushed, HandscrapedContent PCPCEN/TR14823190 x 1900 x 15 mmBreaking Strength N/mm²EN153317 kg / 7.73 kgThermal ConductivityEN12664Biological DurabilityEN350-22.17 m² / 75.95 m²2.17 m² / 75.95 m²CARB2Slip resistanceCEN/TS15676DynamicIts compliantIts compliantWoodloc@ 5GGlue-down, FloatingIts compliantIts compliantYesHardwood / 3.5 mmIts compliantIts compliantIts compliant2-3 timesPine/SpruceIts compliantIts compliantIts compliant

DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | [©]Kährs 2025-09-01

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection









MAPLE CAROB





OAK CONCRETE



OAK STRAW



OAK EARTH

OAK CAMINO