



## OAK STRAW

The naturally oiled finish on this rustic, single-strip oak floor from the Artisan Collection brings out the colour variations in the timber, which range from toasted cinnamon to burnt toffee hues. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

### PRODUCT DETAILS

<b>Article Number</b>	151XCDEKFZKW195
<b>EAN Code</b>	7393969045292
<b>Surface treatment</b>	Oil This floor should be oiled immediately after installation.
<b>Design features</b>	Bevelled 4-sided, Brushed, Handscraped
<b>Dimensions</b>	190 x 1900 mm
<b>Weight per Package</b>	17 kg
<b>Area per Package</b>	2.2 m <sup>2</sup>
<b>Package info</b>	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

### COLOUR CHANGE

Some muting of colour variation to medium, straw brown.


### FACTS

<b>Wood Species</b>	Oak
<b>Design</b>	1-strip
<b>Grading</b>	Dynamic
<b>Range</b>	Kährs Original
<b>Collection</b>	Artisan Collection
<b>Resandable</b>	2-3 times
<b>Natural/Stained</b>	Natural
<b>Joint</b>	Woodloc® 5G
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Warranty US</b>	25 years
<b>Wear-layer material</b>	Hardwood
<b>Wear Layer Thickness</b>	3.5 mm
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness</b>	15 mm
<b>Installation method</b>	Glue-down, Floating
<b>Surface Colour</b>	Rustic natur

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>	>500 kg/m <sup>3</sup>	
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 ppm
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>	.11 (m2K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	
<b>Slip resistance</b>	CEN/TS15676	NPD

Other products in this collection




OAK BUCKSKIN



Maple Carob



Oak Concrete



Oak Tan



Oak Straw




Oak Oyster



Oak Linen



Oak Earth



Oak Camino

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.