



OAK LAVA

The domino black hues in this 3-strip oak floor from the Harmony Collection create a luxurious expression that enhances a range of interiors. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the timber. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

PRODUCT DETAILS

| | |
|---------------------------|---|
| Article Number | 153N6CEK1JKW240 |
| EAN Code | 7393969029629 |
| Surface treatment | Matt lacquer |
| Design features | Brushed |
| Dimensions | 200 x 2423 mm |
| Weight per Package | 23 kg |
| Area per Package | 2.9 m ² |
| Area per pallet | 130.1 m ² |
| Package info | Packages may contain start and stop boards. |

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Stained product - noticeable color change over time.

FACTS

| | |
|-----------------------------|---------------------|
| Wood Species | Oak |
| Design | 3-strip |
| Grading | Lively |
| Range | Kährs Original |
| Collection | Harmony Collection |
| Resandable | 2-3 times |
| Natural/Stained | Stained |
| Brinell Value | 3,7 |
| Joint | Woodloc® 5S |
| Floor heating | Yes |
| Warranty | 30 years |
| Warranty US | 25 years |
| Wear-layer material | Hardwood |
| Wear Layer Thickness | 3.5 mm |
| Core material | Pine/Spruce lamella |
| Thickness | 15 mm |
| Installation method | Glue-down, Floating |
| Surface Colour | Black 1J |

TECHNICAL PROPERTIES

| | | |
|--|--------------------------|-----------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m³ | >500 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | .11 (m ² K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |
| Slip resistance | CEN/TS15676 | NPD |

Other products in this collection



Oak Silk




Oak Shell



Oak Brownie



Oak Alloy




Oak Pale




Oak Ale



Oak Creme



Oak Granite



Oak Dew



Oak Soil



Oak Stone



Oak Limestone



Oak Lava

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.