



OAK BREEZE

The sandy blonde hues found in this 2-strip hard oak floor from the Lodge Collection create a calm and even expression, suitable for a range of interiors. The silk lacquer finish gives the floor a polished appearance bringing out the natural character of the timber. The even finish protects the wood from daily wear, without adding artificial shine.

PRODUCT DETAILS		
Product type / Construction	Wood Floors / Veneer floors	
Article Number / EAN Code	372034EK50KW 0 / 7393969104029	
Design / Wood Species	2-strip / Oak	
Surface treatment /	Satin lacquer / Natural	
Natural/Stained		
Design features	Brushed	
Width x Length x Thickness	193 x 1225 x 7 mm	
Weight per package / per	20 kg / 7.14 kg	
m2		
Area per package / per	2.8 m ² / 113.6 m ²	
pallet		
Grading	Calm	
Joint	Woodloc®	
Installation method	Floating, Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 0.6 mm	
thickness		
Resandable	Not resandable	
Core material	HDF	
Hardness (Brinell) value /	5-6/5-6	
range		

PRODUCT DETAILS

Warranty	12 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>800 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Cfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,22 W/mK
Thermal Resistance R-Value	2	.031 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD













DETAILED DESCRIPTION

Even colour with minor variations.

Small sized knots in limited numbers allowed.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Descriptions & Imagery

