



## GARDEN WALNUT

One strip design, silk matte finish, slight color variation, four sided bevel, may contain some knots. Features Kährs ECO Core.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES	
<b>Article Number</b>	101P3FVA50KW120	<b>Wood Species</b>	Walnut	<b>Moisture content</b>	EN13183 7%±2%
<b>Surface Treatment</b>	Silk matte finish	<b>Design</b>	1-strip	<b>Minimum Mean Density kg/m³</b>	>800 kg/m³
<b>Refining Treatment</b>	Beveled 4-sided	<b>Grading</b>	Variation (Town)	<b>Reaction To Fire</b>	EN13501-1 Cfl-s1
<b>Dimensions</b>	47 1/4 x 5 x 3/8"	<b>Range</b>	Kährs Spirit	<b>Formaldehyde Emission</b>	EN717-1 E1
<b>Weight per Package</b>	31 lbs	<b>Collection</b>	Unity Collection	<b>Content PCP</b>	CEN/TR14823 ≤ 5 x 10-6n
<b>Area per Package</b>	16.14 sq ft	<b>Resandable</b>	1 time	<b>Breaking Strength N/mm²</b>	EN1533 NPĐ
<b>Area Per Board</b>	1.614 sq ft	<b>Natural/Stained</b>	Natural	<b>Thermal Conductivity</b>	EN12664 0,14 W/mK
<b>DETAIL DESCRIPTION</b>		<b>Brinell Value</b>	2,3	<b>Thermal Resistance R-Value</b>	.07 (m2K/W)
Even colour with minor variations. Small sized knots in limited numbers allowed.		<b>Joint</b>	Woodloc®	<b>Biological Durability</b>	EN350-2 Class 1
<b>COLOUR CHANGE</b>		<b>Floor heating</b>	Yes	<b>CARB2</b>	Compliant
Changes to golden brown.		<b>Wear-layer material</b>	Hardwood		
		<b>Wear-layer thickness</b>	5/64"		
		<b>Core material</b>	HDF		
		<b>Thickness</b>	3/8"		
		<b>Installation method</b>	Floating, Glue-Down		

### CERTIFICATES

