



## ORCHARD WALNUT

The deep walnut-brown hue found in this warm single-strip, stained floor from the Unity Collection is enhanced by its natural grain. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

### PRODUCT DETAILS

<b>Article Number</b>	101P6FVA09KW120
<b>Surface treatment</b>	Matt lacquer
<b>Design features</b>	Microbevelled 4-sided
<b>Dimensions</b>	1200 x 125 x 10 mm
<b>Weight per Package</b>	14 kg
<b>Area per Package</b>	1.50 m <sup>2</sup>
<b>Area Per Board</b>	0.150 m <sup>2</sup>

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

Changes to golden brown.

### FACTS

<b>Wood Species</b>	Walnut
<b>Board</b>	1-strip
<b>Grading</b>	Lively (Country)
<b>Range</b>	Kährs Spirit
<b>Collection</b>	Unity Collection
<b>Resandable</b>	1 time
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	2,3
<b>Joint</b>	Woodloc®
<b>Floor heating</b>	Yes
<b>Warranty</b>	20 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	1,9 mm
<b>Core material</b>	HDF
<b>Thickness</b>	10 mm
<b>Installation method</b>	Floating, Glue-down

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>		>800 kg/m <sup>3</sup>
<b>Reaction To Fire</b>	EN13501-1	Cfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.07 (m <sup>2</sup> K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

### CERTIFICATES

