



## OAK BRIGHTON

This single-strip oak floor from the Sand Collection features warm butterscotch undertones, punctuated with naturally occurring knots for a lively expression. The wearing side of each board is taken exclusively from a single piece of wood, capturing the true form of the timber. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

### PRODUCT DETAILS

|                                     |  |
|-------------------------------------|--|
| Product type / Construction         | Wood Floors / 3-layer parquet              |
| Article Number / EAN Code           | 151L87EK0VKW220 / 7393969041164            |
| Design / Wood Species               | Plank / Oak                                |
| Surface treatment / Natural/Stained | Matt lacquer / Stained                     |
| Design features                     | Smooth/ Not brushed                        |
| Width x Length x Thickness          | 187 x 2266 x 15 mm                         |
| Weight per package / per m2         | 21 kg / 8.4 kg                             |
| Area per package / per pallet       | 2.54 m <sup>2</sup> / 114.3 m <sup>2</sup> |
| Grading                             | Lively                                     |
| Joint                               | Woodloc® 5S                                |
| Installation method                 | Floating, Glue-down                        |
| Floor heating                       | Yes  |
| Wear leayer material / thickness    | Hardwood / 3.5 mm                          |
| Resandable                          | 2-3 times                                  |
| Core material                       | Pine/Spruce                                |
| Hardness (Brinell) value / range    | 3,7 / 2.2 - 5.9                            |

### PRODUCT DETAILS

|                |          |
|----------------|----------|
| LRV / LRV Std1 | 42 / 3.5 |
| Warranty       | 30 years |

### TECHNICAL PROPERTIES

|                                     |             |                        |
|-------------------------------------|-------------|------------------------|
| Moisture content                    | EN13183     | 7%±2%                  |
| Minimum Mean Density                |             | >500 kg/m <sup>3</sup> |
| Reaction To Fire                    | EN13501-1   | Dfl-s1                 |
| Formaldehyde Emission               | EN717-1     | E1                     |
| Content PCP                         | CEN/TR14823 | ≤ 5 ppm                |
| Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD                    |
| Thermal Conductivity                | EN12664     | 0,11W/mK               |
| Biological Durability               | EN350-2     | Class 1                |
| CARB2                               |             | Compliant              |
| Slip resistance                     | CEN/TS15676 | NPD                    |



### DETAILED DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers.

**Colour change:** Stained product - noticeable color change over time.

Packages may contain start and stop boards.

### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2026-02-25

## Other products in this collection



OAK AMALFI



OAK RÜGEN



OAK ESTORIL



OAK SORRENTO



OAK PORTOFINO



OAK BRIGHTON



ASH SKAGEN



ASH SANDVIG



ASH FALSTERBO