



ASH CORAL

Coming June 2023 - Ash Coral has a modern yet classic look with tones of warm white corals from sandy beaches. The characteristics of the ash enhance the impression of this matt lacquered 3-strip floor.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	133B11AKLCKW226	Wood Species	Ash	Moisture content	EN13183	7%±2%
EAN Code	7393969048392	Design	3-strip	Minimum Mean Density kg/m³	>500 kg/m³	
Surface Treatment	Matte finish	Grading	Lively	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	7 3/8 x 89 1/4 "	Range	Kährs Avanti	Formaldehyde Emission	EN717-1	E1
Weight per Package	54.1 lbs	Collection	Ground Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	36.7 sqft	Resandable	2 times	Breaking Strength N/mm²	EN1533	NPD
Area per pallet	1284.7 sqft	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Brinell Value	4,0	Thermal Resistance R-Value	.09 (m2K/W)	
		Joint	Woodloc® 5G	Biological Durability	EN350-2	Class 1
		Floor heating	Yes	CARB2	Compliant	
		Warranty	20 years	Slipperiness	CEN/TS15676	NPD
		Wear-layer material	Hardwood			
		Wear Layer Thickness	1/8"			
		Core material	Pine/Spruce lamella			
		Backside material	Spruce			
		Thickness	1/2"			
		Installation method	Floating, Glue-Down			
		LRV	62			

Other products in this collection



OAK CLAY



ASH CORAL



OAK SAND



OAK SEED



OAK CHALK

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.