



OAK SAND

Oak Sand is a beautiful and warm yet light and lively oak floor, reminiscent of warm, sandy beaches. It is a 3-strip, matt lacquered floor with lots of character. Oak Sand is ideal for any interiors, creating a light and homely feeling.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	133B22EK1KKW226	Wood Species	Oak	Moisture	EN13183	7%±2%
EAN Code	7393969048408	Design	3-strip	content		
Surface Treatment	Matt lacquer	Grading	Lively	Minimun Mean Density kg/m³ >500 kg/m³		
Dimensions	188 x 2266 mm	Range	Kährs Avanti	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	24.55 kg	Collection	Ground Collection	Formaldehyde Emission	EN717-1	E1
Area per Package	3.41 m ²	Natural/Stained	Stained			
Area per pallet	119.35 m ²	Brinell Value	3,7	Content PCP	CEN/TR14823	3 ≤ 5 x 10-6n
Package info	Packages may contain start and stop boards.	Joint	Woodloc® 5G	Breaking Strength N/mm²	EN1533	NPD
		Floor heating	Yes			
COLOUR CHANGE		Wear-layer material	Hardwood	Thermal Conductivity	EN12664	0,14 W/mK
Stained product - noticeable colour change over time.		Wear Layer Thickness	2.6 mm			
		Core material	Pine/Spruce lamella	Thermal Resistance R-Value		.09 (m2K/W)
		Backside material	Spruce	Biological Durability	EN350-2	Class 1
			13 mm	CARB2		Compliant
		Installation method	Floating, Glue-down	Slipperiness CEN/TS15670		·
		LRV	40			., 0 141 5

Other products in this collection





ASH CORAL





OAK CLAY





OAK SEED

OAK CHALK

CERTIFICATES









Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.