



# OAK SAND

Oak Sand is a beautiful and warm yet light and lively oak floor, reminiscent of warm, sandy beaches. It is a 3-strip, matt lacquered floor with lots of character. Oak Sand is ideal for any interiors, creating a light and homely feeling.

## PRODUCT DETAILS

|   |   |
|---|---|
| Product type / Construction             | Wood Flooring / 3-layer parquet             |
| Article Number / EAN Code               | 133B22EK1KKW226 / 7393969048408             |
| Design / Wood Species                   | 3-strip / Oak                               |
| Surface Treatment / Natural/Stained     | Matt lacquer / Stained                      |
| Width x Length x Thickness              | 188 x 2266 x 13 mm                          |
| Weight per package / per m <sup>2</sup> | 24.55 kg / 7.2 kg                           |
| Area per package / per pallet           | 3.41 m <sup>2</sup> / 119.35 m <sup>2</sup> |
| Grading                                 | Lively                                      |
| Joint                                   | Woodloc® 5G                                 |
| Installation method                     | Floating, Glue-down                         |
| Floor heating                           | Yes   |
| Wear layer material / thickness         | Hardwood / 2.6 mm                           |
| Resandable                              | 2 times                                     |
| Core material                           | Pine/Spruce lamella                         |
| Backside material                       | Spruce                                      |
| Hardness (Brinell) value / range        | 3,7 / 2.2 - 5.9                             |

## PRODUCT DETAILS

|                |          |
|----------------|----------|
| LRV / LRV Std1 | 39.8 / 4 |
| Warranty       | 20 years |

## TECHNICAL PROPERTIES

|                                     |             |                          |
|-------------------------------------|-------------|--------------------------|
| Moisture content                    | EN13183     | 7%±2%                    |
| Minimum Mean Density                |             | >500 kg/m <sup>3</sup>   |
| Reaction To Fire                    | EN13501-1   | Dfl-s1                   |
| Formaldehyde Emission               | EN717-1     | E1                       |
| Content PCP                         | CEN/TR14823 | ≤ 5 x 10-6n              |
| Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD                      |
| Thermal Conductivity                | EN12664     | 0,14 W/mK                |
| Thermal Resistance R-Value          |             | .09 (m <sup>2</sup> K/W) |
| Biological Durability               | EN350-2     | Class 1                  |
| CARB2                               |             | Compliant                |
| Slip resistance                     | CEN/TS15676 | NPD                      |



## DETAILED DESCRIPTION

**Colour change:** Stained product - noticeable colour change over time.

Packages may contain start and stop boards.

## Descriptions & Imagery


All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs (UK) Ltd |  
www.kahrs.com | ©Kährs,  
United Kingdom & Ireland  
2024-09-19

Other products in this collection



OAK CLAY



ASH CORAL



OAK SAND



OAK SEED



OAK CHALK