

OAK SAND

Oak Sand is a beautiful and warm yet light and lively oak floor, reminiscent of warm, sandy beaches. It is a 3-strip, matt lacquered floor with lots of character. Oak Sand is ideal for any interiors, creating a light and homely feeling.

PRODUCT DETAILS		I
Product type / Construction	Wood Flooring / 3-layer parquet	i
Article Number / EAN Code	133B22EK1KKW226 / 7393969048408	
Design / Wood Species	3-strip / Oak	
Surface Treatment /	Matt lacquer / Stained	
Natural/Stained		
Width x Length x Thickness	188 x 2266 x 13 mm	
Weight per package / per	24.55 kg / 7.2 kg	
m2		
Area per package / per	3.41 m ² / 119.35 m ²	<u>:</u>
pallet		
Grading	Lively	:
Joint	Woodloc® 5G	
Installation method	Floating, Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 2.6 mm	-
thickness		
Resandable	2 times	
Core material	Pine/Spruce lamella	
Backside material	Spruce	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		

PRODUCT DETAILS	
LRV / LRV Std1	

LRV / LRV Std1	39.8 / 4	
Warranty	20 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	2	.09 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD









DETAILED DESCRIPTION

Colour change: Stained product - noticeable colour change over time.

Packages may contain start and stop boards.

Other products in this collection









OAK CLAY

ASH CORAL

OAK SAND

OAK SEED



OAK CHALK