



## OAK SAND

Oak Sand is a beautiful and warm yet light and lively oak floor, bringing your thoughts to summer beaches. It is a 3-strip, matt lacquered floor with lots of character. Oak Sand is ideal for any interior where you are looking for a natural and light floor for a homey feeling.

| PRODUCT DETAILS             |                                    |
|-----------------------------|------------------------------------|
| Product type / Construction | Wood Flooring / 3-layer engineered |
| Article Number / EAN Code   | 133B22EK1KKW226 / 7393969048408    |
| Design / Wood Species       | 3-strip / White Oak                |
| Surface Treatment /         | Matte finish / Stained             |
| Natural/Stained             |                                    |
| Width x Length x Thickness  | 7 3/8 x 89 1/4 x 1/2"              |
| Weight per package / per    | 54.1 lbs / 15.9 lbs                |
| <u>m2</u>                   |                                    |
| Area per package / per      | 36.7 sqft / 1284.7 sqft            |
| pallet                      |                                    |
| Grading                     | Lively                             |
| Joint                       | Woodloc® 5G                        |
| Installation method         | Floating, Glue-Down                |
| Floor heating               | Yes                                |
| Wear leayer material /      | Hardwood / 1/8"                    |
| thickness                   |                                    |
| Resandable                  | 2 times                            |
| Core material               | Pine/Spruce lamella                |
| Backside material           | Spruce                             |
| Hardness (Brinell) value /  | 3,7 / 2.2 - 5.9                    |
| range                       |                                    |

| PRODUCT DETAILS | ROD | UCT | DE. | ΓΑΙ | LS |
|-----------------|-----|-----|-----|-----|----|
|-----------------|-----|-----|-----|-----|----|

| LRV / LRV Std1                      | 40 / 4      |             |
|-------------------------------------|-------------|-------------|
| TECHNICAL PROPERTIES                | 5           |             |
| Moisture content                    | EN13183     | 7%±2%       |
| Minimun Mean Density                |             | >500 kg/m³  |
| kg/m³                               |             |             |
| Reaction To Fire                    | EN13501-1   | Dfl-s1      |
| Formaldehyde Emission               | EN717-1     | E1          |
| Content PCP                         | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD         |
| Thermal Resistance R-Value          | 1           | .09 (m2K/W) |
| Biological Durability               | EN350-2     | Class 1     |
| CARB2                               |             | Compliant   |
| Slip resistance                     | CEN/TS15676 | NPD         |











## Other products in this collection









OAK CLAY

ASH CORAL

OAK SEED

OAK CHALK