

TAKAYNA CLW 218

Kährs Luxury Tiles Click floor Takayna has deep earthy tones, amber and gold highlights, and realistic wood knots and cracks. Takayna is a characterful floor that effortlessly creates a warm, homely atmosphere. The rustic wood impression is enhanced by synchrone embossing, highlighting the grain and texture of the natural wood design.

PRODUCT DETAILS		TECHNICAL PROPERTIES			
Article Number	LTCLW2306-218	Application	EN ISO 10874	23/33/42	
Dimensions	218 x 1210 mm	Effect of furniture leg	EN ISO 16581	No visible damage/Change	
Weight per Package	20.6 kg	Emission of formalder	iyde	E1	
Area per Package	2.1 m ²	Reaction To Fire	EN13501-1	Bfl-s1	₩ B ₁₁ ≤1
Area per pallet	84.4 m ²	Formaldehyde	EN717-1	E1	
Construction	Click 6 mm	Emission			
		Thermal Resistance R-Value		0.035 (m2K/W)	([©] p
DETAIL DESCRIPTION		Residual indentation I	EN ISO 24343-1	< 0.2 mm (*with underlayment)
For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.		Dimensional stability	EN ISO 23999	< 0.1 %	ר א צ צ
		Colour fastness	EN ISO 105- B02	≥ 6	57
		Slip resistance	EN 13893	DS (>0.3)	255- DS-
projects.		Slip resistance	DIN 51130	R10	

FACTS

Design	Wood design
Range	Luxury Tiles
Collection	Nordic Classic Collection
Warranty	30 years residential/15 years commercial

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



TECHNICAL PROPERTIES			
Statical electrical propensity	EN 1815	< 2 kV (antistatic)	Ŧ
Scratch resistance	EN16094	Pass with good results	<u>-</u>
Chemical resistance	EN ISO 26987	Pass with good results	\$ 0
Effect of castor chair	EN 425	Suitable	6
Resistance to bacteria and fungi		Good	
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)	٢
Commercial usage classification	EN 14354:2017	Class 33	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



Other products in this collection



Moesgaard - Click 6 mm



Otago - Click 6 mm

Foloi - Click 6 mm





Akkelis - Click 6 mm



Pando - Click 6 mm



Coconino - Click 6 mm



Takayna - Click 6 mm



Kilsbergen - Click 6 mm



Didnok - Click 6 mm



Blaiken - Click 6 mm



Irati - Click 6 mm

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

