

TAKAYNA CLW 218

Kährs Rigid Click Luxury Tiles floor Takayna has deep earthy tones, amber and gold highlights, and realistic wood knots and cracks. Takayna is a characterful floor that effortlessly creates a warm, homely atmosphere. The rustic wood impression is enhanced by registered embossing, highlighting the grain and texture of the natural wood design.

PRODUCT DETAILS			TECHNICAL PROPERTIES		
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		Thermal Resistance R-Value		0.035 (m2K/W)
Article Number / EAN Code	LTCLW2306-218 / 7393969114752		Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
Design	Tile Design				underlayment)
Width x Length x Thickness	218 x 1210 x 6 mm		Dimensional stability	EN ISO 23999	< 0.1 %
Weight per package / per	20.6 kg / 9.81 kg		Colour fastness	EN ISO 105-B02	≥ 6
m2			Slip resistance	EN 13893	DS (>0.3)
Area per package / per	2.1 m ² / 84.4 m ²		Slip resistance	DIN 51130	R10
pallet			Statical electrical	EN 1815	< 2 kV (antistatic)
Joint	Click5G		propensity		
Installation method	Floating		Scratch resistance	EN16094	Pass with good results
Floor heating	Yes		Chemical resistance	EN ISO 26987	Pass with good results
Wear leayer thickness	0.55 mm		Resistance to bacteria and		Good
Warranty	30 years residential/15 years commercial		fungi		
TECHNICAL PROPERTIES			Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE underlayment)
Application	EN ISO 10874	23/33/42	Commencial	EN 4 42E 4-2017	, , , , , , , , , , , , , , , , , , ,
Emission of formaldehyde		E1	— Commercial usage — classification	EN 14354:2017	Class 33
Reaction To Fire	EN13501-1	Bfl-s1			
Formaldehyde Emission	EN717-1	E1	M12 score	Construction of the second sec	

DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kahrs (UK) Ltd | www.kahrs.com | [©]Kährs, United Kingdom & Ireland 2025-07-05

Other products in this collection



MOESGAARD - CLICK 6 MM



OTAGO - CLICK 6 MM



FOLOI - CLICK 6 MM



THURINGIAN - CLICK 6 MM



AKKELIS - CLICK 6 MM



KILSBERGEN - CLICK 6 MM



COCONINO - CLICK 6 MM



TAKAYNA - CLICK 6 MM



DIDNOK - CLICK 6 MM



BLAIKEN - CLICK 6 MM