



DIDNOK CLICK 6 MM

Kährs Luxury Tiles Click floor Didnok with deep dark shades of grey and a rustic wood appearance is a true statement floor that perfectly complements any interior. A realistic wood grain and authentic knots and cracks give the floor an expressive impression. The skilfully created wood appearance is enhanced by synchrone embossing for a natural look and feel.

PRODUCT DETAILS Product type / Construction Luxury Vinyl Tiles and Planks / Click SPC LVT Article Number / EAN Code LTCLW2309-218 / 7393969114783 Design Plank Width x Length x Thickness 218 x 1210 x 6 mm Weight per package / per 20.6 kg / 9.81 kg 2.11 m² / 84.4 m² Area per package / per pallet Joint Click5G Installation method Floating Floor heating Yes Wear leayer thickness 0.55 mm Warranty 30 years residential/15 years commercial **TECHNICAL PROPERTIES** EN ISO 10874 **Application** 23/33/42 Effect of furniture leg EN ISO 16581 No visible damage/Change >1800 mm Impact resistance Emission of formaldehyde E1

TECHNICAL	PROPERTIES
-----------	-------------------

Reaction To Fire	EN13501-1	Bfl-s1
Formaldehyde Emission	EN717-1	E1
Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation EN		< 0.2 mm (*with
ISO 24343-1		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable (25.000 cycles)
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		











DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Other products in this collection





THURINGIAN CLICK



COCONINO CLICK



DIDNOK CLICK



OTAGO CLICK





TAKAYNA CLICK



BLAIKEN CLICK



FOLOI CLICK



KILSBERGEN CLICK