



## KILSBERGEN CLICK 6 MM

Kährs Rigid Click Luxury Tiles floor Kilsbergen has a light natural oak design, softened by a transparent white stain, resulting in a timeless floor that complements any interior. The natural oak colour, wood grain and visible knots and cracks create an authentic look, enhanced by registered embossing. The decor features a rich variety of colors and tones, creating a visually dynamic surface.

## **PRODUCT DETAILS** Product type / Construction Luxury Vinyl Tiles and Planks / Click SPC LVT Article Number / EAN Code LTCLW2302-218 / 7393969114714 1-strip Design Width x Length x Thickness 218 x 1210 x 6 mm Weight per package / per 20.6 kg / 9.81 kg 2.11 m<sup>2</sup> / 84.4 m<sup>2</sup> Area per package / per pallet Click5G Joint Installation method Floating Floor heating Yes Wear leayer thickness 0.55 mm Warranty 30 years residential/15 years commercial **TECHNICAL PROPERTIES** EN ISO 10874 23/33/42 Application Emission of formaldehyde F1 Reaction To Fire EN13501-1 Bfl-s1 Formaldehyde Emission EN717-1 E1

TECHNICAL	PROPERTIES
-----------	------------

Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 <b>Δ</b> Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		
		(UVD











## **DETAILED DESCRIPTION**

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

## Other products in this collection



KILSBERGEN CLICK