



ASPEN CLICK 6 MM

Kährs Luxury Tiles Click floor Aspen was inspired by white tropical beaches, a floor with a natural creamy white stain and silky feeling. Soft, gentle hues enhance the natural patterns of the wood design, including natural features such as knots and cracks.

PRODUCT DETAILS

| | |
|-------------------------------|---|
| Product type / Construction | Luxury Vinyl Tiles and Planks / Click SPC LVT |
| Article Number / EAN Code | LTCLW2121-218 / 7393969114684 |
| Design | Plank |
| Width x Length x Thickness | 218 x 1210 x 6 mm |
| Weight per package / per m2 | 20.6 kg / 9.81 kg |
| Area per package / per pallet | 2.11 m ² / 84.4 m ² |
| Joint | Click5G |
| Installation method | Floating |
| Floor heating | Yes |
| Wear leayer thickness | 0.55 mm |
| Warranty | 30 years |

TECHNICAL PROPERTIES

| | | |
|--------------------------|--------------|--------------------------|
| Application | EN ISO 10874 | 23/33/42 |
| Effect of furniture leg | EN ISO 16581 | No visible damage/Change |
| Impact resistance | | >1800 mm |
| Emission of formaldehyde | | E1 |

TECHNICAL PROPERTIES

| | | |
|-------------------------------------|----------------|-------------------------------|
| Reaction To Fire | EN13501-1 | Bfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Thermal Resistance R-Value | | 0.035 (m2K/W) |
| Residual indentation EN ISO 24343-1 | | < 0.2 mm (*with underlayment) |
| Dimensional stability | EN ISO 23999 | < 0.1 % |
| Colour fastness | EN ISO 105-B02 | ≥ 6 |
| Slip resistance | EN 13893 | DS (>0.3) |
| Slip resistance | DIN 51130 | R10 |
| Statical electrical propensity | EN 1815 | < 2 kV (antistatic) |
| Scratch resistance | EN16094 | Pass with good results |
| Chemical resistance | EN ISO 26987 | Pass with good results |
| Effect of castor chair | EN 425 | Suitable (25.000 cycles) |
| Resistance to bacteria and fungi | | Good |
| Impact sound reduction | EN ISO 10140 | 20 ΔLw dB (IXPE underlayment) |
| Commercial usage classification | EN 14354:2017 | Class 33 |



DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2026-02-09

Other products in this collection



ASPEN CLICK



SAPO CLICK



SAXON CLICK 6 MM



REDWOOD CLICK 6 MM



SAREK CLICK 6 MM



OULANKA CLICK 6 MM



TAIGA CLICK 6 MM