



0.035 (m2K/W)

20 **Δ**Lw dB (IXPE underlayment)

Class 33

ASPEN CLICK 6 MM

Kährs Rigid Click Luxury Tiles floor Aspen was inspired by white tropical beaches, a floor with a natural creamy white stain and silky feeling. Soft, gentle hues enhance the natural patterns of the wood design, including natural features such as knots and cracks.

PRODUCT DETAILS			TECHNICAL PROPERTIES	
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		Thermal Resistance R-Value	
Article Number / EAN Code	LTCLW2121-218 / 7393969114684		Residual indentation	
Design	1-strip			
Width x Length x Thickness	218 x 1210 x 6 mm		Dimensional stability	
Weight per package / per	20.6 kg / 9.81 kg		Colour fastness	
m2			Slip resistance	
Area per package / per	2.11 m ² / 84.4 m ²		Slip resistance	
pallet			Statical electrical	
Joint	Click5G		propensity	
Installation method	Floating		Scratch resistance	
Floor heating	Yes		Chemical resistance	
Wear leayer thickness	0.55 mm		Effect of castor chair	
Warranty	30 years		Resistance to bacteria and	
TECHNICAL PROPERTIES		fungi		
Application	EN ISO 10874	23/33/42	Impact sound reduction	
Emission of formaldehyde		E1		
Reaction To Fire	EN13501-1	Bfl-s1	Commercial usage	
Formaldehyde Emission	EN717-1	E1	- classification	

Residual indentation		EN ISO 24343-1	< 0.2 mm (*with
_			underlayment)
Dimen	sional stability	EN ISO 23999	< 0.1 %
Colour	fastness	EN ISO 105-B02	≥ 6
Slip res	sistance	EN 13893	DS (>0.3)
Slip res	sistance	DIN 51130	R10
Statica	l electrical	EN 1815	< 2 kV (antistatic)
proper	nsity		
Scratch	n resistance	EN16094	Pass with good results
Chemi	cal resistance	EN ISO 26987	Pass with good results
Effect	of castor chair	EN 425	Suitable (25.000 cycles)
Resistance to bacteria and		Good	









EN ISO 10140

EN 14354:2017



DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Other products in this collection







SAPO CLICK



SAXON CLICK 6 MM



REDWOOD CLICK 6 MM



SAREK CLICK 6 MM



OULANKA CLICK 6 MM



TAIGA CLICK 6 MM