



## **ASPEN CLW 218**

DDODLICT DETAILS

Kährs Rigid Click Luxury Tiles floor Aspen was inspired by white tropical beaches, a floor with a natural creamy white stain and silky feeling. Soft, gentle hues enhance the natural patterns of the wood design, including natural features such as knots and cracks.

PRODUCT DETAILS			TECHNICAL PROPERTIES
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		Thermal Resistance R-Value
Article Number / EAN Code	LTCLW2121-218 / 7393969114684		Residual indentation
Design	Tile Design		<del>-</del>
Width x Length x Thickness	218 x 1210 x 6 mm		Dimensional stability
Weight per package / per	20.6 kg / 9.81 kg		Colour fastness
m2			Slip resistance
Area per package / per	2.1 m <sup>2</sup> / 84.4 m <sup>2</sup>		Slip resistance
pallet			Statical electrical
Joint	Click5G		propensity
Installation method	Floating		Scratch resistance
Floor heating	Yes		Chemical resistance
Wear leayer thickness	0.55 mm		Resistance to bacteria and
Warranty	30 years		fungi
TECHNICAL PROPERTIES			Impact sound reduction
Application	EN ISO 10874	23/33/42	<del>-</del>
Emission of formaldehyde		E1	Commercial usage
Reaction To Fire	EN13501-1	Bfl-s1	- classification
Formaldehyde Emission	EN717-1	E1	- gresion coast

Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 <b>∆</b> Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		











## **DETAILED DESCRIPTION**

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

## Other products in this collection



ASPEN - CLICK 6 MM



SAPO - CLICK 6 MM



SAXON - CLICK 6 MM



REDWOOD - CLICK 6 MM



SAREK - CLICK 6 MM



OULANKA - CLICK 6 MM



TAIGA - CLICK 6 MM