



## AKKELIS CLICK 6 MM

Kährs Luxury Tiles Click floor Akkelis has rich shades of brown and subtle tones of gold and amber, Akkelis is a characterful wood design floor with a warm impression. The rustical wood graining, knots and cracks are enhanced by synchrone embossing for a truly authentic wood look.

### PRODUCT DETAILS

Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT
Article Number / EAN Code	LTCLW2305-218 / 7393969114745
Design	Plank
Width x Length x Thickness	218 x 1210 x 6 mm
Weight per package / per m <sup>2</sup>	20.6 kg / 9.81 kg
Area per package / per pallet	2.11 m <sup>2</sup> / 84.4 m <sup>2</sup>
Joint	Click5G
Installation method	Floating
Floor heating	Yes
Wear leayer thickness	0.55 mm
Warranty	30 years residential/15 years commercial

### TECHNICAL PROPERTIES

Application	EN ISO 10874	23/33/42
Effect of furniture leg	EN ISO 16581	No visible damage/Change
Impact resistance		>1800 mm
Emission of formaldehyde	E1	

### TECHNICAL PROPERTIES

Reaction To Fire	EN13501-1	Bfl-s1
Formaldehyde Emission	EN717-1	E1
Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation EN ISO 24343-1		< 0.2 mm (*with underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical propensity	EN 1815	< 2 kV (antistatic)
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable (25.000 cycles)
Resistance to bacteria and fungi		Good
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)
Commercial usage classification	EN 14354:2017	Class 33



### DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2026-05-01

Other products in this collection



MOESGAARD CLICK



THURINGIAN CLICK



COCONINO CLICK



DIDNOK CLICK



OTAGO CLICK



AKKELIS CLICK



TAKAYNA CLICK



BLAIKEN CLICK



FOLOI CLICK



KILSBERGEN CLICK