



## **IRATI CLICK 6 MM**

Kährs Luxury Tiles Click floor Irati with its creamy white and greyish hues has been inspired by sandy dunes and fresh morning. Irati is a floor that brings warmth and brightness to any space. Cracks and knots are skilfully designed and enhanced by synchrone embossing to create a realistic rustic wood look.

PRODUCT DETAILS			TECHNICAL PROPERTIES		
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		Formaldehyde Emission	EN717-1	E1
Article Number / EAN Code	LTCLW2301-218 / 7393969114707		Thermal Resistance R-Value		0.035 (m2K/W)
Design	Plank		Residual indentation EN		< 0.2 mm (*with
Width x Length x Thickness	218 x 1210 x 6 mm		ISO 24343-1		underlayment)
Weight per package / per	20.6 kg / 9.81 kg		Dimensional stability	EN ISO 23999	< 0.1 %
m2			Colour fastness	EN ISO 105-B02	≥ 6
Area per package / per	2.11 m <sup>2</sup> / 84.4 m <sup>2</sup>		Slip resistance	EN 13893	DS (>0.3)
pallet			Slip resistance	DIN 51130	R10
Joint	Click5G		Statical electrical	EN 1815	< 2 kV (antistatic)
Installation method	Floating		propensity		
Floor heating	Yes		Scratch resistance	EN16094	Pass with good result
Wear leayer thickness	0.55 mm		Chemical resistance	EN ISO 26987	Pass with good result
Warranty	30 years residential/15 years commercial		Effect of castor chair	EN 425	Suitable
TECHNICAL PROPERTIES			Resistance to bacteria and fungi		Good
Application	EN ISO 10874	23/33/42	Impact sound reduction	EN ISO 10140	20 <b>Δ</b> Lw dB (IXPE
Effect of furniture leg	EN ISO 16581	No visible damage/Change	Impact sound reduction	EN 130 10140	,
Emission of formaldehyde		E1	Carrananial	EN 442E4-2047	underlayment)
Reaction To Fire	EN13501-1	Bfl-s1	<ul><li>Commercial usage</li><li>classification</li></ul>	EN 14354:2017	Class 33











## DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

## Other products in this collection





THURINGIAN CLICK



COCONINO CLICK



DIDNOK CLICK



OTAGO CLICK





TAKAYNA CLICK



BLAIKEN CLICK



FOLOI CLICK



KILSBERGEN CLICK