



IRATI CLW 218

PRODUCT DETAILS

Kährs Rigid Click Luxury Tiles floor Irati with its creamy white and greyish hues has been inspired by sandy dunes and fresh morning. Irati is a floor that brings warmth and brightness to any space. Cracks and knots are skilfully designed and enhanced by registered embossing to create a realistic rustic wood look.

PRODUCT DETAILS			
Product type / Construction	Luxury Vinyl Tiles and	Planks / Click SPC LVT	Т
Article Number / EAN Code	LTCLW2301-218 / 7393969114707		R
Design	Tile Design		
Width x Length x Thickness	218 x 1210 x 6 mm		D
Weight per package / per	20.6 kg / 9.81 kg		С
m2			SI
Area per package / per	2.1 m ² / 84.4 m ²		SI
pallet			St
Joint	Click5G		р
Installation method	Floating		S
Floor heating	Yes		С
Wear leayer thickness	0.55 mm		R
Warranty	30 years residential/15	years commercial	fu
TECHNICAL PROPERTIES			In
Application	EN ISO 10874	23/33/42	
Emission of formaldehyde		E1	— С
Reaction To Fire	EN13501-1	Bfl-s1	cl
Formaldehyde Emission	EN717-1	E1	

TECHNICAL PROPERT	IES
-------------------	-----

Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		











DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Other products in this collection



MOESGAARD - CLICK 6 MM



THURINGIAN - CLICK 6 MM



COCONINO - CLICK 6 MM



DIDNOK - CLICK 6 MM



OTAGO - CLICK 6 MM



AKKELIS - CLICK 6 MM



TAKAYNA - CLICK 6 MM



BLAIKEN - CLICK 6 MM



FOLOI - CLICK 6 MM



KILSBERGEN - CLICK 6 MM