



## IRATI - CLICK 6 MM

Kährs Rigid Click Luxury Tiles floor Irati with its creamy white and greyish hues has been inspired by sandy dunes and fresh morning. Irati is a floor that brings warmth and brightness to any space. Cracks and knots are skilfully designed and enhanced by registered embossing to create a realistic rustic wood look.

### PRODUCT DETAILS

|  |                      |
|--|----------------------|
| <b>Article Number</b>                  | LTCLW2301-218        |
| <b>Dimensions</b>                      | 1210 x 218 x 6 mm    |
| <b>Weight per Package</b>              | 20.6 kg              |
| <b>Area per Package</b>                | 2.1 m <sup>2</sup>   |
| <b>Area Per Board</b>                  | 0.264 m <sup>2</sup> |
| <b>Area per pallet (m<sup>2</sup>)</b> | 84.4 m <sup>2</sup>  |
|  | Click 6 mm           |

### FACTS

|                            |                             |
|----------------------------|-----------------------------|
| <b>Design</b>              | Wood design                 |
| <b>Range</b>               | Luxury Tiles                |
| <b>Collection</b>          | Nordic Classic Collection   |
| <b>Joint</b>               | Click5G                     |
| <b>Floor heating</b>       | Yes                         |
|                            | IXPE Sound reducing backing |
|                            | 6 mm                        |
| <b>ColourCode</b>          | 1                           |
| <b>Installation method</b> | Floating                    |

### TECHNICAL PROPERTIES

|   |                                     |
|---|-------------------------------------|
| <b>Application</b>                      | EN ISO 23/33/42<br>10874            |
| <b>Reaction To Fire</b>                 | EN13501- Bfl-s1<br>1                |
| <b>Thermal Resistance R-Value</b>       | 0.035 (m <sup>2</sup> K/W)          |
| <b>Statical electrical propensity</b>   | EN 1815 < 2 kV<br>(antistatic)      |
| <b>Scratch resistance</b>               | EN16094 Pass with good results      |
| <b>Chemical resistance</b>              | EN ISO 26987 Pass with good results |
| <b>Resistance to bacteria and fungi</b> | Does not act as substrate           |

### DETAIL DESCRIPTION


For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



## Other products in this collection




Didnok - Click 6 mm



Otago - Click 6 mm



Akkelis - Click 6 mm



Takayna - Click 6 mm



Blaiken - Click 6 mm



Foloji - Click 6 mm



Pando - Click 6 mm



Kilsbergen - Click 6 mm



Irati - Click 6 mm

### Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*

