



## FONTIN CLICK 6 MM

DDODLICT DETAILS

Kährs Luxury Tiles Click floor Fontin has been inspired by the warm brown and golden tones of a calm summer sunset. The truly authentic natural impression is enhanced by a subtle wood design grading, making Fontin a stunning, timeless floor.

PRODUCT DETAILS			
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		
Article Number / EAN Code	LTCLW2009-218 / 7393969114677		
Design	Plank		
Width x Length x Thickness	218 x 1210 x 6 mm		
Weight per package / per	20.6 kg / 9.81 kg		
m2			
Area per package / per	2.11 m <sup>2</sup> / 84.4 m <sup>2</sup>		
pallet			
Joint	Click5G		
	Floating		
Installation method	Floating		
Installation method Floor heating	Floating Yes		
-			
Floor heating	Yes		
Floor heating Wear leayer thickness	Yes 0.55 mm		
Floor heating Wear leayer thickness Warranty	Yes 0.55 mm	23/33/42	
Floor heating Wear leayer thickness Warranty TECHNICAL PROPERTIES	Yes 0.55 mm 30 years	23/33/42  No visible damage/Change	
Floor heating Wear leayer thickness Warranty TECHNICAL PROPERTIES Application	Yes 0.55 mm 30 years EN ISO 10874		
Floor heating Wear leayer thickness Warranty TECHNICAL PROPERTIES Application Effect of furniture leg	Yes 0.55 mm 30 years EN ISO 10874	No visible damage/Change	

TECHNICAL FROM EIGHES		
Reaction To Fire	EN13501-1	Bfl-s1
Formaldehyde Emission	EN717-1	E1
Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation EN		< 0.2 mm (*with
ISO 24343-1		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable (25.000 cycles)
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 <b>Δ</b> Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		











## **DETAILED DESCRIPTION**

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

## Other products in this collection







HANMER CLICK



WHINFELL CLICK 6 MM



YUKON CLICK



TIVEDEN CLICK

WENTWOOD CLICK