



FONTIN CLW 218

Kährs Rigid Click Luxury Tiles floor Fontin has been inspired by the warm brown and golden tones of a calm summer sunset. The truly authentic natural impression is enhanced by a subtle wood design grading, making Fontin a stunning, timeless floor.

PRODUCT DETAILS

| | |
|-------------------------------|--|
| Product type / Construction | Luxury Vinyl Tiles / Click 6 mm |
| Article Number / EAN Code | LTCLW2009-218 / 7393969114677 |
| Design | Wood design |
| Width x Length x Thickness | 218 x 1210 x 6 mm |
| Weight per package / per m2 | 20.6 kg / 9.81 kg |
| Area per package / per pallet | 2.1 m ² / 84.4 m ² |
| Floor heating | Yes |
| Wear leayer thickness | 0.55 mm |

TECHNICAL PROPERTIES

| | | |
|----------------------------|----------------|-------------------------------|
| Application | EN ISO 10874 | 23/33/42 |
| Emission of formaldehyde | | E1 |
| Reaction To Fire | EN13501-1 | Bfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Thermal Resistance R-Value | | 0.035 (m2K/W) |
| Residual indentation | EN ISO 24343-1 | < 0.2 mm (*with underlayment) |
| Dimensional stability | EN ISO 23999 | < 0.1 % |

TECHNICAL PROPERTIES

| | | |
|----------------------------------|----------------|-------------------------------|
| Colour fastness | EN ISO 105-B02 | ≥ 6 |
| Slip resistance | EN 13893 | DS (>0.3) |
| Slip resistance | DIN 51130 | R10 |
| Statical electrical propensity | EN 1815 | < 2 kV (antistatic) |
| Scratch resistance | EN16094 | Pass with good results |
| Chemical resistance | EN ISO 26987 | Pass with good results |
| Resistance to bacteria and fungi | | Good |
| Impact sound reduction | EN ISO 10140 | 20 ΔLw dB (IXPE underlayment) |
| Commercial usage classification | EN 14354:2017 | Class 33 |



DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs (UK) Ltd |
www.kahrs.com | ©Kährs,
United Kingdom & Ireland
2024-07-27

Other products in this collection



Fontin - Click 6 mm



Hanmer - Click 6 mm



Whinfell - Click 6 mm



Yukon - Click 6 mm



Tiveden - Click 6 mm



Wentwood - Click 6 mm