

PANDO CLICK 6 MM

Kährs Luxury Tiles Click floor Pando is inspired by the dense, mysterious forests of Scandinavia. Pando features dark, earthy shades of brown and a realistic rustic wood design – perfectly complementing contemporary and traditional interiors. Knots, cracks, and wood grain are enhanced by synchrone embossing, for an authentic wood look and feel.

PRODUCT DETAILS			TECHNICAL PROPERTIES		
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		Formaldehyde Emission	EN717-1	E1
Article Number / EAN Code	LTCLW2307-218 / 7393969114769		Thermal Resistance R-Value		0.035 (m2K/W)
Design	Plank		Residual indentation EN		< 0.2 mm (*with
Width x Length x Thickness	218 x 1210 x 6 mm		ISO 24343-1		underlayment)
Weight per package / per	20.6 kg / 9.81 kg		Dimensional stability	EN ISO 23999	< 0.1 %
m2			Colour fastness	EN ISO 105-B02	≥6
Area per package / per	2.11 m ² / 84.4 m ²		Slip resistance	EN 13893	DS (>0.3)
pallet			Slip resistance	DIN 51130	R10
Joint	Click5G		Statical electrical	EN 1815	< 2 kV (antistatic)
Installation method	Floating		propensity		
Floor heating	Yes		Scratch resistance	EN16094	Pass with good results
Wear leayer thickness	0.55 mm		Chemical resistance	EN ISO 26987	Pass with good results
Warranty	30 years residential/15 years commercial		Effect of castor chair	EN 425	Suitable
TECHNICAL PROPERTIES			Resistance to bacteria and		Good
Application	EN ISO 10874	23/33/42	fungi		
Effect of furniture leg	EN ISO 16581	No visible damage/Change	 Impact sound reduction 	EN ISO 10140	20 ∆ Lw dB (IXPE
Emission of formaldehyde		E1			underlayment)
Reaction To Fire	EN13501-1	Bfl-s1	 Commercial usage 	EN 14354:2017	Class 33
			- classification		

DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

score (E

Descriptions & Imagery

www.kahrs.com | [©]Kährs 2025-08-25

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



MOESGAARD CLICK



THURINGIAN CLICK



AKKELIS CLICK



FOLOI CLICK





COCONINO CLICK



TAKAYNA CLICK



DIDNOK CLICK



BLAIKEN CLICK