

PANDO CLW 218

Kährs Luxury Tiles Click floor Pando is inspired by the dense, mysterious forests of Scandinavia. Pando features dark, earthy shades of brown and a realistic rustic wood design – perfectly complementing contemporary and traditional interiors. Knots, cracks, and wood grain are enhanced by synchrone embossing, for an authentic wood look and feel.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES			
Article Number	LTCLW2307-218	Design	Wood design	Application	EN ISO	23/33/42	
Dimensions	218 x 1210 mm	Range	Luxury Tiles		10874		
Weight per Package	20.6 kg	Collection	Nordic Classic	Effect of furniture leg	EN ISO 16581	No visible damage/Change	2
Area per Package	2.1 m ²		Collection	Emission of		E1	
Area per pallet	84.4 m ²	Joint	Click5G	formaldehyde			
Construction	Click 6 mm	Floor heating	Yes	Reaction To	EN13501- 1	Bfl-s1	Burst
		Warranty	30 years	Fire			Birst
DETAIL DESCRIPTION		,	residential/15 years commercial	Formaldehyde Emission	EN717-1	E1	
For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate- free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.		Thickness	6 mm	Thermal Resist	Thermal Resistance R- 0.035 (m2K/W)		
		Installation method	Floating	Value			
				Residual indentation EN ISO 24343-1		< 0.2 mm (*with underlayment)	Ĩ.
				Dimensional stability	EN ISO 23999	< 0.1 %	רא רא
				Colour fastness	EN ISO 105-B02	≥ 6	57
				Slip resistance	EN 13893	DS (>0.3)	Ka-
				Slip resistance	DIN 51130	R10	SET.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



TECHNICAL PROPERTIES

Statical electrical propensity	EN 1815	< 2 kV (antistatic)	Ŧ
Scratch resistance	EN16094	Pass with good results	B
Chemical resistance	EN ISO 26987	Pass with good results	<u>ی</u>
Effect of castor chair	EN 425	Suitable	6
Resistance to ba fungi	cteria and	Good	
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)	٢
Commercial usage classification	EN 14354:2017	Class 33	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



Other products in this collection



Moesgaard - Click 6 mm



Otago - Click 6 mm

Foloi - Click 6 mm





Akkelis - Click 6 mm



Pando - Click 6 mm



Coconino - Click 6 mm



Takayna - Click 6 mm



Kilsbergen - Click 6 mm



Didnok - Click 6 mm



Blaiken - Click 6 mm



Irati - Click 6 mm

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

