



PANDO - CLICK 6 MM

Kährs Luxury Tiles Click floor Pando is inspired by the dense, mysterious forests of Scandinavia. Pando features dark, earthy shades of brown and a realistic rustic wood design – perfectly complementing contemporary and traditional interiors. Knots, cracks, and wood grain are enhanced by synchronic embossing, for an authentic wood look and feel.

PRODUCT DETAILS

Article Number	LTCLW2307-218
Dimensions	1210 x 218 x 6 mm
Weight per Package (kg)	20.6 kg
Area per Package (m²)	2.1 m ²
Area Per Board	0.264 m ²
Area per pallet (m²)	84.4 m ²
Construction	Click 6 mm

FACTS

Design	Wood design
Range	Luxury Tiles
Collection	Nordic Classic Collection
Joint	Click5G
Floor heating	Yes
Thickness (mm)	6 mm
ColourCode	5
Installation method	Floating

TECHNICAL PROPERTIES

Application	EN ISO 10874	23/33/42
Reaction To Fire	EN13501-1	Bfl-s1
Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation EN ISO 24343-1 (2.5 h)		< 0.2 mm (*with underlayment)
Dimensional stability	EN ISO 23999 (80 °C/6 h)	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical propensity	EN 1815	< 2 kV (antistatic)
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results

DETAIL DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

TECHNICAL PROPERTIES


Effect of castor chair	EN 425	Suitable
Resistance to bacteria and fungi		Does not act as substrate
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



Other products in this collection



Didnok - Click 6 mm



Otago - Click 6 mm



Akkelis - Click 6 mm



Takayna - Click 6 mm



Blaiken - Click 6 mm



Foloji - Click 6 mm



Pando - Click 6 mm



Kilsbergen - Click 6 mm



Irati - Click 6 mm

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

