



PANDO CLW 218

DDODLICT DETAILS

Kährs Rigid Click Luxury Tiles floor Pando is inspired by the dense, mysterious forests of Scandinavia. Pando features dark, earthy shades of brown and a realistic rustic wood design – perfectly complementing contemporary and traditional interiors. Knots, cracks, and wood grain are enhanced by registered embossing, for an authentic wood look and feel.

PRODUCT DETAILS			
Product type / Construction	Luxury Vinyl Tiles / Click 6 mm		
Article Number / EAN Code	LTCLW2307-218 / 7393969114769		
Design	Wood design		_
Width x Length x Thickness	218 x 1210 x 6 mm		
Weight per package / per	20.6 kg / 9.81 kg		
m2			
Area per package / per	2.1 m ² / 84.4 m ²		
pallet			
Joint	Click5G		
Installation method	Floating		
Floor heating	Yes		
Wear leayer thickness	0.55 mm		
Warranty	30 years residential/15 years commercial		
TECHNICAL PROPERTIES			
Application	EN ISO 10874	23/33/42	
Emission of formaldehyde		E1	(
Reaction To Fire	EN13501-1	Bfl-s1	
Formaldehyde Emission	EN717-1	E1	

Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		











DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Other products in this collection



Pando - Click 6 mm

Kilsbergen - Click 6 mm

Irati - Click 6 mm