



FOLOI CLICK 6 MM

DDODLICT DETAILS

Kährs Luxury Tiles Click floor Foloi is inspired by the beauty of freshly sawn oak wood, Foloi features warm, natural colours that create a homely atmosphere in any interior. The natural look is enhanced by a skilfully created wood design, featuring knots and cracks that are accentuated by synchrone embossing.

PRODUCT DETAILS			I ECHNICAL I
Product type / Construction	Luxury Vinyl Tile	s and Planks / Click SPC LVT	Formaldehyde
Article Number / EAN Code	LTCLW2304-218 / 7393969114738		Thermal Resist
Design	Plank		Residual inden
Width x Length x Thickness	218 x 1210 x 6	mm	ISO 24343-1
Weight per package / per	20.6 kg / 9.81 kg	g	Dimensional st
m2			Colour fastnes
Area per package / per	2.11 m ² / 84.4 n	m ²	Slip resistance
pallet			Slip resistance
Joint	Click5G		Statical electric
Installation method	Floating		propensity
Floor heating	Yes		Scratch resista
Wear leayer thickness	0.55 mm		Chemical resis
Warranty	30 years resider	ntial/15 years commercial	Effect of castor
TECHNICAL PROPERTIES			Resistance to l
Application	EN ISO 10874	23/33/42	fungi
Effect of furniture leg	EN ISO 16581	No visible damage/Change	mpact sound
Emission of formaldehyde		E1	
Reaction To Fire	EN13501-1	Bfl-s1	Commercial us
-			 classification

TECHNICAL PROPERTIES		
Formaldehyde Emission	EN717-1	E1
Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation EN		< 0.2 mm (*with
ISO 24343-1		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33











DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Descriptions & Imagery

Other products in this collection





THURINGIAN CLICK



COCONINO CLICK



DIDNOK CLICK



OTAGO CLICK





TAKAYNA CLICK



BLAIKEN CLICK



FOLOI CLICK



KILSBERGEN CLICK