



E1

Pass with good results

Suitable

FOLOI CLW 218

Kährs Luxury Tiles Click floor Foloi is inspired by the beauty of freshly sawn oak wood, Foloi features warm, natural colours that create a homely atmosphere in any interior. The natural look is enhanced by a skilfully created wood design, featuring knots and cracks that are accentuated by synchrone embossing.

PRODUCT DETAILS			TECHNICAL PROPERTIES
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		Formaldehyde Emission
Article Number / EAN Code	LTCLW2304-218 / 7393969114738		Thermal Resistance R-Value
Design	Tile Design		Residual indentation EN
Width x Length x Thickness	218 x 1210 x 6 mm		ISO 24343-1
Weight per package / per	20.6 kg / 9.81 kg		Dimensional stability
m2			Colour fastness
Area per package / per	2.1 m ² / 84.4 m ²		Slip resistance
pallet			Slip resistance
Joint	Click5G		Statical electrical
Installation method	Floating		propensity
Floor heating	Yes		Scratch resistance
Wear leayer thickness	0.55 mm		Chemical resistance
Warranty	30 years residential/15 years commercial		Effect of castor chair
TECHNICAL PROPERTIES			Resistance to bacteria and
 Application	EN ISO 10874	23/33/42	- fungi
Effect of furniture leg	EN ISO 16581	No visible damage/Change	 Impact sound reduction
Emission of formaldehyde		E1	
Reaction To Fire	EN13501-1	Bfl-s1	Commercial usage
			 classification

Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation EN		< 0.2 mm (*with
ISO 24343-1		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results

EN ISO 26987

EN 425

EN717-1













DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Other products in this collection



MOESGAARD - CLICK 6 MM



THURINGIAN - CLICK 6 MM



COCONINO - CLICK 6 MM



DIDNOK - CLICK 6 MM



OTAGO - CLICK 6 MM



AKKELIS - CLICK 6 MM



TAKAYNA - CLICK 6 MM



BLAIKEN - CLICK 6 MM



FOLOI - CLICK 6 MM



KILSBERGEN - CLICK 6 MM