



# FOLOI CLW 218

Kährs Rigid Click Luxury Tiles floor Foloi is inspired by the beauty of freshly sawn oak wood, Foloi features warm, natural colours that create a homely atmosphere in any interior. The natural look is enhanced by a skilfully created wood design, featuring knots and cracks that are accentuated by registered embossing.

## PRODUCT DETAILS

<b>Article Number</b>	LTCLW2304-218
<b>Dimensions</b>	218 x 1210 mm
<b>Weight per Package</b>	20.6 kg
<b>Area per Package</b>	2.1 m <sup>2</sup>
<b>Area per pallet</b>	84.4 m <sup>2</sup>
	Click 6 mm

## DETAIL DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

## FACTS

<b>Design</b>	Wood design
<b>Range</b>	Luxury Tiles
<b>Collection</b>	Nordic Classic Collection
<b>Joint</b>	Click5G
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years residential/15 years commercial
	6 mm
<b>Installation method</b>	Floating

## TECHNICAL PROPERTIES


<b>Application</b>	EN ISO 23/33/42	10874	
<b>Reaction To Fire</b>	EN13501- Bfl-s1	1	
<b>Thermal Resistance R-Value</b>	0.035 (m2K/W)		
<b>Residual indentation</b>	EN ISO 24343-1	< 0.2 mm (*with underlayment)	
<b>Dimensional stability</b>	EN ISO 23999	< 0.1 %	
<b>Colour fastness</b>	EN ISO 105-B02	≥ 6	
<b>Slip resistance</b>	EN 13893	DS (>0.3)	
<b>Slip resistance</b>	DIN 51130	R10	
<b>Statical electrical propensity</b>	EN 1815	< 2 kV (antistatic)	
<b>Scratch resistance</b>	EN16094	Pass with good results	
<b>Chemical resistance</b>	EN ISO 26987	Pass with good results	

## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



## TECHNICAL PROPERTIES

<b>Resistance to bacteria and fungi</b>		Good	
<b>Impact sound reduction</b>	EN ISO 10140	20 ΔLw dB (IXPE underlayment)	
<b>Commercial usage classification</b>	EN 14354:2017	Class 33	

## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



## Other products in this collection



Moesgaard - Click 6 mm



Thuringian - Click 6 mm



Coconino - Click 6 mm



Didnok - Click 6 mm



Otago - Click 6 mm



Akkelis - Click 6 mm




Takayna - Click 6 mm



Blaiken - Click 6 mm



Foloi - Click 6 mm



Pando - Click 6 mm



Kilsbergen - Click 6 mm



Irati - Click 6 mm

### Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*