



HANMER CLICK 6 MM

Kährs Luxury Tiles Click floor Hanmer combines the colours of natural oak wood with nuances from warm sand, Hanmer has a truly authentic, natural look. With warm nuances and a calm grade wood design, the floor effortlessly creates an relaxing atmosphere in any interior.

PRODUCT DETAILS			
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		
Article Number / EAN Code	LTCLW2010-218 / 7393969114660		
Design	Plank		
Width x Length x Thickness	218 x 1210 x 6 mm		
Weight per package / per	20.6 kg / 9.81 kg		
m2			
Area per package / per	2.11 m ² / 84.4 m ²		
pallet			
Joint	Click5G		
Installation method	Floating		
Floor heating	Yes		
Wear leayer thickness	0.55 mm		
Warranty	30 years		
TECHNICAL PROPERTIES		_	
Application	EN ISO 10874	23/33/42	
Effect of furniture leg	EN ISO 16581	No visible damage/Change	
Impact resistance		>1800 mm	
Emission of formaldehyde	_	E1	

Reaction To Fire	EN13501-1	Bfl-s1
Formaldehyde Emission	EN717-1	E1
Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation EN		< 0.2 mm (*with
ISO 24343-1		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable (25.000 cycles)
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		











DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Other products in this collection







HANMER CLICK



WHINFELL CLICK 6 MM



YUKON CLICK



TIVEDEN CLICK

WENTWOOD CLICK