



# HANMER CLW 218

Kährs Luxury Tiles Click floor Hanmer combines the colours of natural oak wood with nuances from warm sand, Hanmer has a truly authentic, natural look. With warm nuances and a calm grade wood design, the floor effortlessly creates an relaxing atmosphere in any interior.

PRODUCT DETAILS		FACTS		TECHNICAL PROPE	RTIES		
Article Number	LTCLW2010-218	Design	Wood design	Application	EN ISO	23/33/42	122,1
Dimensions	218 x 1210 mm	Range	Luxury Tiles		10874		
Weight per Package	20.6 kg	Collection	Breeze Collection	Effect of furniture leg	EN ISO 16581	No visible damage/Change	<u> </u>
Area per Package	2.1 m <sup>2</sup>	Joint	Click5G	Emission of		E1	
Area per pallet	84.4 m <sup>2</sup>	Floor heating	Yes	formaldehyde			
Construction	Click 6 mm	Backside material	IXPE Sound reducing backing	Reaction To Fire	EN13501- 1	Bfl-s1	B <sub>H</sub> -S1
DETAIL DESCRIPTION		Thickness	6 mm	Formaldehyde Emission	EN717-1	E1	
For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system,		Installation method	Floating	Thermal Resistance R- 0.035 (m		0.035 (m2K/W)	
enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate- free and have IXPE sound reducing backing,						< 0.2 mm (*with underlayment)	Ţ
effectively controlling noise	0 0			Dimensional	EN ISO	< 0.1 %	K N K N

### **Descriptions & Imagery**

ideal for renovation projects.

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.







strong ceramic coating resistant to wear, scratching

and water. Can be installed on an existing floor,



stability

Colour

fastness

Slip resistance

Slip resistance

23999

EN ISO

105-B02

DIN

51130

EN 13893 DS (>0.3)

R10

#### **TECHNICAL PROPERTIES**

TECHNICAL PROPERTIES							
Statical electrical propensity	EN 1815	< 2 kV (antistatic)	<i>F</i>				
Scratch resistance	EN16094	Pass with good results					
Chemical resistance	EN ISO 26987	Pass with good results	€				
Effect of castor chair	EN 425	Suitable	6				
Resistance to bac	cteria and	Good					
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)					
Commercial usage classification	EN 14354:2017	Class 33					

#### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.











## Other products in this collection



Fontin - Click 6 mm



Hanmer - Click 6 mm



Whinfell - Click 6 mm



Yukon - Click 6 mm



Tiveden - Click 6 mm



Wentwood - Click 6 mm

#### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.







