



## BACKA

Rich and warm tones from amber creates a generous and luxurious ambiance.

### PRODUCT DETAILS

|                           |   |
|---------------------------|---|
| <b>Article Number</b>     | 153N66EK02KW240                                   |
| <b>Surface Treatment</b>  | Oil   |
| <b>Refining Treatment</b> | Bevelled 4-sided, Handscraped, Brushed, Saw marks |
| <b>Dimensions</b>         | 2419 x 196 x 15 mm                                |
| <b>Weight per Package</b> | 22,4 kg   |
| <b>Area per Package</b>   | 2.84 m <sup>2</sup>                               |
| <b>Area Per Board</b>     | 0,474 m <sup>2</sup>                              |

### DETAIL DESCRIPTION

Contains knots and all natural colour variations.

### COLOUR CHANGE

The colour matures over time

### FACTS

|                            |                     |
|----------------------------|---------------------|
| <b>Wood Species</b>        | Oak                 |
| <b>Design</b>              | 3-strip             |
| <b>Grading</b>             | Dynamic             |
| <b>Range</b>               | Kährs Original      |
| <b>Collection</b>          | Götaland Collection |
| <b>Natural/Stained</b>     | Stained             |
| <b>Brinell Value</b>       | 3,7                 |
| <b>Joint</b>               | Woodloc® 5S         |
| <b>Floor heating</b>       | Yes                 |
| <b>Wear-layer material</b> | Hardwood            |
| <b>Core material</b>       | Pine/Spruce/Alder   |
| <b>Thickness</b>           | 15 mm               |
| <b>Installation method</b> | Floating, Glue-down |

### TECHNICAL PROPERTIES

|  |             |                          |
|--|-------------|--------------------------|
| <b>Moisture content</b>                      | EN13183     | 7%±2%                    |
| <b>Minimum Mean Density kg/m<sup>3</sup></b> |             | >500 kg/m <sup>3</sup>   |
| <b>Reaction To Fire</b>                      | EN13501-1   | Dfl-s1                   |
| <b>Formaldehyde Emission</b>                 | EN717-1     | E1                       |
| <b>Content PCP</b>                           | CEN/TR14823 | ≤ 5 x 10 <sup>-6</sup> n |
| <b>Breaking Strength N/mm<sup>2</sup></b>    | EN1533      | NPD                      |
| <b>Thermal Conductivity</b>                  | EN12664     | 0,14 W/mK                |
| <b>Thermal Resistance R-Value</b>            |             | .11 (m <sup>2</sup> K/W) |
| <b>Biological Durability</b>                 | EN350-2     | Class 1                  |
| <b>CARB2</b>                                 |             | Compliant                |

### CERTIFICATES

