

**Kährs®**



## GROOVE

### PRODUCT DETAILS

<b>Article Number</b>	101P8HVAF0KW180
<b>Surface Treatment</b>	Oil
<b>Refining Treatment</b>	Brushed, Handscraped, Microbeveled 4-sided
<b>Dimensions</b>	72" x 5 x 3/8"
<b>Weight per Package</b>	37 lbs
<b>Area per Package</b>	19,69 sq ft
<b>Area Per Board</b>	2,454 sq ft

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

Changes to golden brown.

### CERTIFICATES

### FACTS

<b>Wood Species</b>	Walnut
<b>Design</b>	1-strip
<b>Grading</b>	Dynamic
<b>Range</b>	Kährs Spirit
<b>Collection</b>	Rugged Collection
<b>Resandable</b>	1 time
<b>Natural/Stained</b>	Natural
<b>Joint</b>	Woodloc®
<b>Floor heating</b>	Yes
<b>Warranty</b>	20 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	5/64"
<b>Core material</b>	HDF
<b>Thickness</b>	3/8"
<b>Installation method</b>	Floating, Glue-Down

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m³</b>		>800 kg/m³
<b>Reaction To Fire</b>	EN13501-1	Cfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.07 (m2K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

