



## SAND OAK

The calming coral hue of this single-strip oak floor in the Unity Collection is lifted by pale white highlights, sand-colour lowlights and a few scattered knots. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

### PRODUCT DETAILS

<b>Article Number</b>	101P3AEKBCKW180
<b>Surface treatment</b>	Matt lacquer
<b>Design features</b>	Bevelled 4-sided, Brushed
<b>Dimensions</b>	1830 x 125 x 10 mm
<b>Weight per Package</b>	16,75 kg
<b>Area per Package</b>	1.83 m <sup>2</sup>
<b>Area Per Board</b>	0.228 m <sup>2</sup>

### DETAIL DESCRIPTION

Even colour with minor variations. Small sized knots in limited numbers allowed.

### COLOUR CHANGE

Stained product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	Oak
<b>Board</b>	1-strip
<b>Grading</b>	Variation (Town)
<b>Range</b>	Kährs Spirit
<b>Collection</b>	Unity Collection
<b>Resandable</b>	1 time
<b>Natural/Stained</b>	Stained
<b>Joint</b>	Woodloc®
<b>Floor heating</b>	Yes
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	1,9 mm
<b>Core material</b>	HDF
<b>Thickness</b>	10 mm
<b>Installation method</b>	Glue-down, Floating
<b>Surface Colour</b>	White BC

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>		>800 kg/m <sup>3</sup>
<b>Reaction To Fire</b>	EN13501-1	Cfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.07 (m <sup>2</sup> K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

### CERTIFICATES

