



FROSTED OAT STRIP

Frosted Oat Strip is inspired by late autumn grain fields covered in frost. The soft white transparent stain allows the rustic wood to enhance the natural design, completed with an ultra-matte finish.

PRODUCT DETAILS		PRODUCT DE
Product type / Construction	Wood Flooring / 3-layer engineered	Hardness (Brine
Article Number / EAN Code	153N6BEKN4KW240 / 7393969048347	range
Design / Wood Species	3-strip / White Oak	LRV / LRV Std1
Surface Treatment /	Ultra matt lacquer / Stained	TECHNICAL P
Natural/Stained		Moisture conte
Refining Treatment	Brushed	— Minimun Mean
Width x Length x Thickness	7 7/8 x 95 3/8 x 5/8"	— kg/m³
Weight per package / per	50.7 lbs / 17.4 lbs	Reaction To Fire
m2		— Formaldehyde
Area per package / per	31.3 sqft / 1409.5 sqft	Content PCP
pallet		Breaking Streng
Grading	Lively	— Biological Dural
Joint	Woodloc® 5S	— CARB2
Installation method	Floating, Glue-Down	
Floor heating	Yes	Slip resistance
Wear leayer material /	Hardwood / 1/8"	TSCA TITLE VI
thickness		CARB P2
Resandable	2 times	Compliant
Core material	Pine/Spruce/Alder	
Backside material	Spruce Veneer	

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
LRV / LRV Std1	39 / 4.7	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant









CEN/TS15676



NPD

DETAILED DESCRIPTION

Naturally occuring wood color variations allowed, from light to dark brown. Sapwood will occur. The product includes medium size black knots. Knots may vary in size and numbers.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Other products in this collection

