



FROSTED OAT STRIP

Frosted Oat Strip is inspired by late autumn grain fields covered in frost. The soft white transparent stain allows the rustic wood to enhance the natural design, completed with an ultra-matte finish.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer engineered	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	153N6BEKN4KW240 / 7393969048347	range		
Design / Wood Species	3-strip / White Oak	LRV / LRV Std1	39 / 4.7	
Surface Treatment /	Ultra matt lacquer / Stained	TECHNICAL PROPERTIES		
Natural/Stained		Moisture content	EN13183	7%±2%
Refining Treatment	Brushed	— Minimun Mean Density	ENTOTOS	>500 kg/m ³
Width x Length x Thickness	7 7/8 x 95 3/8 x 5/8"	— kg/m ³		>300 kg/III
Weight per package / per	50.7 lbs / 17.4 lbs	Reaction To Fire	EN13501-1	Dfl-s1
m2		Formaldehyde Emission	EN717-1	E1
Area per package / per	31.3 sqft / 1409.5 sqft	Content PCP	CEN/TR14823	≤ 5 x 10-6n
pallet		Breaking Strength N/mm ²	EN1533	NPD
Grading	Lively	— Thermal Resistance R-Value		.11 (m2K/W)
Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Installation method	Floating, Glue-Down	— CARB2	LINDO-Z	Compliant
Floor heating	Yes		CEN/TS15676	NPD
Wear leayer material /	Hardwood / 1/8"	Slip resistance	CEIV/13150/6	NYU
thickness		TSCA TITLE VI		
Resandable	2 times	CARB P2	Phil Comment	
Core material	Pine/Spruce/Alder	Compliant (43/VM ON)	SCS Global Services	
Backside material	Spruce Veneer			

DETAILED DESCRIPTION

Naturally occurring wood color variations allowed, from light to dark brown. Sapwood will occur. The product includes medium size black knots. Knots may vary in size and numbers.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Other products in this collection

