



## OAK OYSTER

A rustic, hand scraped product. White coloured and natural oil. the boards may contain large knots and cracks. This product must be oiled after installation and prior to use.

### PRODUCT DETAILS

<b>Article Number</b>	151XCDEKFKW195
<b>Surface Treatment</b>	Oil
<b>Refining Treatment</b>	Beveled 4-sided, Brushed, Handscraped
<b>Dimensions</b>	74 13/16 x 7 15/32 x 19/32"
<b>Weight per Package</b>	38 lbs
<b>Area per Package</b>	23.36 sq ft
<b>Area Per Board</b>	3.886 sq ft

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

Stained product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	White Oak
<b>Design</b>	1-strip
<b>Grading</b>	Dynamic
<b>Range</b>	Kährs Original
<b>Collection</b>	Artisan Collection
<b>Resandable</b>	2 times
<b>Natural/Stained</b>	Stained
<b>Joint</b>	Woodloc® 5G
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	1/8"
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness</b>	19/32"
<b>Installation method</b>	Glue-Down, Floating
<b>Surface Color</b>	White

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m³</b>		>500 kg/m³
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.11 (m2K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

### CERTIFICATES

