

ZERO TILE 5112 CONCRETE

Zero Tile can create a monolithic look for large spaces or make a statement by mixing and matching colors. Installation is fast and the end result will look elegant as well as pleasing to the eye without welded joints.

PRODUCT DETAILS		TECHNICAL PROPERTIES		
Article Number	5112	Reaction To Fire	EN13501-1	Bfl-s1
Dimensions	19 5/8 x 19 5/8 "	Residual indentation	EN ISO 24343-1	< 0.05 mm
Weight per Package	38.6 lbs	Slip resistance	EN 13893	DS (>0.3)
Area per Package	53.8 sqft	Slip resistance	DIN 51130	R9
FACTS		Statical electrical propensity	EN 1815	< 2 kV (antistatic)
Use	Assisted living, Daycare, Education, Healthcare, Office			
	Tiles			
Range	Luxury Tiles			
Collection	Zero Tile			
Thickness	1/8"			
	Grey			
LRV	36			

Other products in this collection



CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.