



Compliant

DS

R10

MSR-A2

underlayer)

< 0.2 mm (*with underlayment) < 0.15 % (80 °C/6 h)

< 2 kV (antistatic)

17 ∆Lw dB (Integrated cork

KAPPADOKIEN CLA 200

The beige highlights and brown rustic foundation of the Kappadokien fairy chimney tops inspired the unique Aware colour Kappadokien. With the authentic wood colours and spot on features such as knots, and cracks makes it the perfect floor for any romantic space.

PRODUCT DETAILS		TECHNICAL PROPERTIES
Product type / Construction	Hybrid Flooring / Click PVC Free LVT	CARB2
Article Number / EAN Code	LTAWAW1112 / 6438117716707	Residual indentation
Design	1-strip	
Width x Length x Thickness	200 x 1815 x 9 mm	Dimensional stability
Weight per package / per	15.84 kg / 7.3 kg	Slip resistance
m2		Slip resistance
Area per package / per	2.17 m ² / 104.16 m ²	Statical electrical
pallet		propensity
Joint	Uniclic®	Scratch resistance
Installation method	Floating	Impact sound reduction
Floor heating	Yes	
Warranty	30 years residential/15 years commercial	SALESION COASTS DIRECT CONTINUE PRINTERS FOOT

EN ISO 10874

EN13501-1

EN717-1

EN12664

USSION CLAS	
2 M 1 \ 3	
*IAIT\	
do will	







EN ISO 24343-1

EN ISO 23999

EN 13893

DIN 51130

EN 1815

EN16094

EN ISO 10140



DETAILED DESCRIPTION

Formaldehyde Emission

Thermal Conductivity

TECHNICAL PROPERTIES

Emission of formaldehyde

Application

Reaction To Fire

A durable, bio-based, natural luxury tiles floor, designed to withstand family-life as well as wear and tear of commercial applications (usage class 33), with the style, beauty and feel of a wooden floor. Based on reclaimed, recycled, and natural fibers. With a water resistant surface, elastic properties for high comfort and good acoustic properties with an integrated cork backing.

CL 23/33

0.118 W/(m*K)

E1

E1

Cfl-s1

Other products in this collection



SERENGETI CLA 200



ROCKY CLA 200



YELLOWSTONE CLA 200



SMOKY CLA 200



GRAND CANYON CLA 200



KAPPADOKIEN CLA 200



BWINDI CLA 200



JASPER CLA 200



YOSEMITE CLA 200