

YELLOWSTONE CLA 200

The rainbow-like colours of Yellowstone dominated by a fiery coffee brown hue enhances the rustic patterns of this wood design, and it includes natural features such as knots and cracks making it the right choice for any interior

PRODUCT DETAILS		TECHNICAL PROPERTIES		
Hybrid Flooring / Click PVC Free LVT		CARB2		Compliant
LTAWAW1117 / 6438117716752		Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
1-strip				underlayment)
200 x 1815 x 9 mm		Dimensional stability	EN ISO 23999	< 0.15 % (80 °C/6 h)
15.84 kg / 7.3 kg		Slip resistance	EN 13893	DS
		Slip resistance	DIN 51130	R10
2.17 m ² / 104.16 m ²		Statical electrical	EN 1815	< 2 kV (antistatic)
		propensity		
Uniclic®		Scratch resistance	EN16094	MSR-A2
Floating		Impact sound reduction	EN ISO 10140	17 Δ Lw dB (Integrated cork
Yes				underlayer)
30 years residential/15 years commercial		SION Cr.		b
		M1 Score) (E 🤇	
EN ISO 10874	CL 23/33	og₁tyw 0 ⁴ / [™]	ices (www.bisuer-er	ngel.de/12176)
	E1			
EN13501-1	Cfl-s1			
EN717-1	E1			
EN12664	0.118 W/(m*K)			
	LTAWAW1117 / 64: 1-strip 200 x 1815 x 9 mm 15.84 kg / 7.3 kg 2.17 m ² / 104.16 m Uniclic® Floating Yes 30 years residentia EN ISO 10874 EN13501-1 EN717-1	LTAWAW1117 / 6438117716752 1-strip 200 x 1815 x 9 mm 15.84 kg / 7.3 kg 2.17 m ² / 104.16 m ² Uniclic® Floating Yes 30 years residential/15 years commercial EN ISO 10874 CL 23/33 E1 EN 1501-1 Cfl-s1 EN717-1 E1	Hybrid Flooring / Click PVC Free LVT CARB2 LTAWAW1117 / 6438117716752 Residual indentation 1-strip Dimensional stability 200 x 1815 x 9 mm Dimensional stability 15.84 kg / 7.3 kg Slip resistance 2.17 m² / 104.16 m² Statical electrical propensity Uniclic® Scratch resistance Floating Impact sound reduction Yes So years residential/15 years commercial EN ISO 10874 CL 23/33 E1 E1 EN717-1 E1	Hybrid Flooring / Click PVC Free LVT CARB2 LTAWAW1117 / 6438117716752 Residual indentation EN ISO 24343-1 1-strip Pinensional stability EN ISO 23999 200 x 1815 x 9 mm Dimensional stability EN ISO 23999 15.84 kg / 7.3 kg Slip resistance EN 13893 2.07 m² / 104.16 m² Statical electrical EN 1815 propensity Uniclic® EN 180 10140 Yes Scratch resistance EN ISO 10140 Yes Impact sound reduction EN ISO 10140 Yes En ISO 10874 CL 23/33 E1 EN ISO 10874 CL 23/33 E1 E1 EN13501-1 Cfl-s1 E1 E1

DETAILED DESCRIPTION

A durable, bio-based, natural luxury tiles floor, designed to withstand family-life as well as wear and tear of commercial applications (usage class 33), with the style, beauty and feel of a wooden floor. Based on reclaimed, recycled, and natural fibers. With a water resistant surface, elastic properties for high comfort and good acoustic properties with an integrated cork backing.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kahrs (UK) Ltd | www.kahrs.com | [©]Kährs, United Kingdom & Ireland 2025-08-15

Other products in this collection



SERENGETI CLA 200



ROCKY CLA 200



KAPPADOKIEN CLA 200



YELLOWSTONE CLA 200



BWINDI CLA 200



SMOKY CLA 200



JASPER CLA 200



YOSEMITE CLA 200