



## GRAND CANYON CLA 200

Combining the colours of the deep valleys of Grand Canyon with warm colours of nature, Grand Canyon has a truly authentic rustic natural look with an ultrasoft feel. The rustic but warm nuances create an effortless natural atmosphere in any interior.

| Hybrid Flooring / Click PVC Free LVT<br>LTAWAW1113 / 6438117716714 | (   |
|--|---|
| I TAMAM/1112 / 6/2011771671/                                       |   |
| LIAWAWIII3/043011//10/14   | F   |
| 1-strip  |   |
| 200 x 1815 x 9 mm  |   |
| 15.84 kg / 7.3 kg  |   |
|  | 9   |
| 2.17 m <sup>2</sup> / 104.16 m <sup>2</sup>                        |   |
|  | ŗ   |
| Uniclic®   |   |
| Floating   | i   |
| Yes  |   |
| 30 years residential/15 years commercial                           |   |
|  | 200 x 1815 x 9 mm<br>15.84 kg / 7.3 kg<br>2.17 m <sup>2</sup> / 104.16 m <sup>2</sup><br>Uniclic®<br>Floating |

| TECHNICAL PROPERTIES     |              |               |
|--------------------------|--------------|---------------|
| Application              | EN ISO 10874 | CL 23/33      |
| Emission of formaldehyde |              | E1            |
| Reaction To Fire         | EN13501-1    | Cfl-s1        |
| Formaldehyde Emission    | EN717-1      | E1            |
| Thermal Conductivity     | EN12664      | 0.118 W/(m*K) |

## TECHNICAL PROPERTIES

| CARB2                  |                | Compliant                          |
|------------------------|----------------|------------------------------------|
| Residual indentation   | EN ISO 24343-1 | < 0.2 mm (*with                    |
| •                      |                | underlayment)                      |
| Dimensional stability  | EN ISO 23999   | < 0.15 % (80 °C/6 h)               |
| Slip resistance        | EN 13893       | DS                                 |
| Slip resistance        | DIN 51130      | R10                                |
| Statical electrical    | EN 1815        | < 2 kV (antistatic)                |
| propensity             |                |                                    |
| Scratch resistance     | EN16094        | MSR-A2                             |
| Impact sound reduction | EN ISO 10140   | 17 <b>∆</b> Lw dB (Integrated cork |
| •                      |                | underlayer)                        |











## **DETAILED DESCRIPTION**

DDODLICT DETAILS

A durable, bio-based, natural luxury tiles floor, designed to withstand family-life as well as wear and tear of commercial applications (usage class 33), with the style, beauty and feel of a wooden floor. Based on reclaimed, recycled, and natural fibers. With a water resistant surface, elastic properties for high comfort and good acoustic properties with an integrated cork backing.

## Other products in this collection



SERENGETI CLA 200



ROCKY CLA 200



YELLOWSTONE CLA 200



SMOKY CLA 200



GRAND CANYON CLA 200



KAPPADOKIEN CLA 200



BWINDI CLA 200



JASPER CLA 200



YOSEMITE CLA 200